



SPECIFICATIONS FOR FIXED-MOUNTED INFRARED TEMPERATURE SENSOR

ENVIRO-THERM™

OPTIMIZED FOR MEASURING PLANT-FOLIAGE SURFACE TEMPERATURE

TEMPERATURE MEASUREMENT

SCALE RANGE:	-10°C TO 100°C
RESOLUTION:	0.1°C
ACCURACY:	±0.3°C FROM -10°C TO 50°C & ±0.5°C OVER 50°C & UNDER 100°C
REPEATABILITY:	±0.1°C
TEMPERATURE:	ALL FUNCTIONS IN °C
NOISE EFFECTIVE TEMPERATURE:	±0.2°C

OPTICAL CONSIDERATIONS

SPECTRAL PASS BAND:	8 < WAVELENGTHS < 14 MICRONS
SIGHTING:	LINE-OF-SIGHT
FIELD OF VIEW:	STANDARD: 10° OPTIONAL: 5° AND 2° AVAILABLE AT ADDITIONAL COST

OPERATING CONDITIONS

OPERATING ENVIRONMENT:	-40°C TO 100°C UP TO 99% RELATIVE HUMIDITY, NON-CONDENSING
STORAGE TEMPERATURE:	SAME AS OPERATING ENVIRONMENT TEMPERATURE
SEALING:	HERMETICALLY SEALED. ONE SOLID BLOCK OF PLASTIC; INHERENTLY WATERPROOF

ELECTRICAL INTERFACE

POWER REQUIREMENTS:	4.8V TO 15V DC. 90 VAC - 250 VAC, 50/60 HZ
OUTPUT SIGNAL:	STANDARD: ANALOG: MILLIVOLT (10mV/°C) DIGITAL: USB 2.0 I²C FORMAT OPTIONAL: TYPE K THERMOCOUPLE

GENERAL

RESPONSE TIME:	.75 SECOND
EMISSION COMPENSATION:	PRESET TO PLANT FOLIAGE EMISSION (0.98)
SKY RADIATION DETECTION/ CORRECTION	STANDARD SKY-SPY™ SYSTEM FOR DETECTION & CORRECTION OF UNWANTED SKY REFLECTION
OPERATING DISTANCE:	2 CM TO 300 METERS
DIMENSIONS:	1" DIAMETER BY 2.5" LENGTH
WARRANTY:	ONE-YEAR LIMITED WARRANTY ON PARTS AND LABOR

EVEREST HAS A POLICY OF CONTINUED DESIGN UPGRADE. THEREFORE, WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

EVEREST INFRARED THERMOMETRY

2010 N Forbes Blvd, Suite 102, Tucson, AZ 85745

(888)736-7349

Website: www.lightsensetechnology.com